



Technical specifications (EN)

WiikHall Aluminium Structure 10 x 32 metres
Framework Aluminium

Cover White PVC-coated polyester with extra UV protection

Doors
 One lace-up fabric door 4.5 x 4 metres (w x h)
 and one fabric folding door 4.5 x 4 metres (w x h)

Ventilation

Two air vents in each gable

Wind load capacity 0.65 Kn/sq.m
 (about 31 m/s) when the building is attached to the ground in accordance with the assembly instructions

Snow load capacity 75 kg/sq.m when the building is attached to the ground in accordance with the assembly instructions

Exterior dim ~

Width	10000
Lengt	32000
Side height	3350
Gable height	5500
Arch distance	4000
Weight per 10 x 32 metres	2.975 kg





Contact information



O.B Wiik Norge (N)

O.B.Wiik AS,
Industriveien 13,
2020 Skedsmokorset,
Telefon +47 64 83 55 00
Telefaks +47 64 83 55 01
www.obwiik.no
E-post obw@obwiik.no

O.B Wiik Sverige (SE)

O.B.Wiik AB,
Borrvägen 3,
155 93 Nykvarn
Telefon +46 (0)8 649 80 80
Telefaks +46 (0)8 649 80 79
www.obwiik.se
E-post obw@obwiik.se

O.B Wiik Denmark (DK)

O.B.Wiik AS
Hasselvej 10
4780 Stege
Tlf.: +45 70 20 34 75
Fax: +45 70 20 34 76
www.obwiik.dk
E-post obw@obwiik.dk

O.B Wiik International (EN)

O.B.Wiik AS,
Industriveien 13,
2020 Skedsmokorset,
Telephone +47 64 83 55 00,
Fax +47 64 83 55 01
www.obwiik.com
E-mail obw@obwiik.com